

CP-LNC-TC51ML4C-MD-L

5MP Dual Light Network Bullet Camera - 40Mtr.

- 1/2.8" 5MP PS CMOS Image Sensor (0.9071 Centimeter)
- Max. 5MP (2616 x 1964)@30fps
- H.265+, H.265, H.264+, H.264, JPEG, AVI encoding
- WDR(120db), Day/night(ICR),3D DNR, ROI, BLC
- IR Range of 40 Mtr, Warm Light Range of 30 Mtr, Red & Blue strobe light
- 3.6mm (2.8mm and 6mm optional)
- Support Built-in Mic and Speaker
- Support SD Card, IP67, PoE
- Support Motion Detection



System Overview

With features of simple installation, easy operation, and high performance-cost ratio, This Series camera is applicable to small, medium and high-sized scenes, such as homes/residences, small-sized retail stores, and other small, medium and high-sized enterprises.

Functions

Power over Ethernet

This product uses the latest PoE technology to troubleshoot the occurrence of any issues in the system making it easier to use. With the help of this technology, your camera now only consumes energy directly from the power supply and doesn't require any mid-way switches.



CP-LNC-TC51ML4C-MD-L

5MP Dual Light Network Bullet Camera - 40Mtr.

Functions

Regions of interest

Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas.

IP67

The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes

True Day/Night (ICR)

When the scene is too dark, the image is captured by illuminating an infrared light through the camera onto the scene that greatly helps with making the scene visible for the lens. It delivers color images during the day and automatically switches to the monochrome feature as the scene darkens.

Motion Detection

When moving objects appear in the monitoring image, CP Plus Motion Detection technology triggers alarm or records.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedeted levels even when compared to international competitors.



CP-LNC-TC51ML4C-MD-L

5MP Dual Light Network Bullet Camera - 40Mtr.

Feature	Specification
Image Sensor	1/2.8" 5MP PS CMOS Image Sensor (0.9071 Centimeter)
Minimum Illumination	Color: 0.006 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Effective Pixels	5MP (2616 x 1964)
Shutter Speed	Auto: 1/3-1/100000 Sec
Lens	3.6mm (2.8mm and 6mm optional)
Max. Aperture	F1.6
S/N Ratio	60dB
Video Compression	H.265+, H.265, H.264+, H.264, JPEG, AVI
Angle of View	2.8 mm: Horizontal 106°, Vertical 56°, Diagonal 127° 3.6 mm: Horizontal 80°, Vertical 56°, Diagonal 107° 6 mm: Horizontal 54°, Vertical 29°, Diagonal 62°
Back Light Compensation	BLC/ WDR (120dB)
Resolution	5 MP
Video Output	Network
Frame Rate	Main Stream: 5MP(2592 x 1944)@30fps, 4MP(2560 x 1440)@30fps, 2MP(1920 x 1080) @30fps/ (1280 x 720)@30fps Sub Stream: 960P(1280 x 720)@30fps, 720P(720 x 480)@30fps
Motion detection	Support (support enable the detection based on human movement only)
Privacy Mask	3 Rectangular Zone
Corridor Pattern	Support
ROI	Support
Reset Button	Support
Image Config	Saturation/ Brightness/ Contrast / Sharpness, Mirror, 3D DNR, White Balance, Anti Flicker, Video Tampering, HLC
Recording Mode	NVR/ CMS/ Web
Day/Night	Color/ B&W (IR-CUT)

Feature	Specification
Audio Compression	G711A/U
TV System	PAL/ NTSC
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, NTP, SMTP, UDP, SNMP, QoS, 802.1x, ONVIF 19.12(Profile S/T), P2P
IR Cut Filter	Support
Ethernet	RJ-45 (10/100Base-T)
Smart Phone	iPhone, Android
Browser	IE8-11, Google Chrome, Firefox, Mac Safari
White LED Number	IR LED: 42μ x 2PCS, Warm light LED: 42μ x 2PCS
IR	IR Range of 40 Mtr.
Warm Light	Warm Light Range of 30 Mtr.
POE	Internal, Support IEEE 802.3af
Focus Control	Fixed
Audio	Built-in Mic and Speaker
Storage	SD card Slot external, Support Max 1TB
IVS (Perimeter Protection)	Intrusion Detection (based on human and Vehicle Detection), Line Cross Detection (based on human and Vehicle Detection), Loiter Detection (based on human detection), People Gather Detection (based on human detection), Motion detection based on human detection, Enter Area (based on human and Vehicle Detection), Leave Area (based on human and vehicle Detection)
Power Source	DC12V, PoE(802.3af)
Weatherproof Standard	IP67
Operating Temperature	-30°C~ +60°C
Operating Humidity	Less than 95%RH
Storage Temperature	-30°C~ +60°C
Storage Humidity	Less than 95%RH
Casing	Metal
Dimension	67.4 mm x 67.7 mm x 164.6 mm
Weight	0.665 g

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com

