

CP-LSC-T24ML3

2.4MP IR Bullet Camera - 30Mtr.

- 1/3" 2.4MP PS CMOS Image Sensor (0.84667 centimeter)
- Max.2.4MP (1920 x 1080)@30fps/25fps
- DWDR, Day/Night, AGC, White Balance, 3D DNR
- 3.6mm Fixed Lens
- IR Range of 30 Mtr., IP67
- Support OSD Menu



System Overview

With features of simple installation, easy operation, and high performance-cost ratio, This Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.



CP-LSC-T24ML3

2.4MP IR Bullet Camera - 30Mtr.

Functions

True Day/Night (ICR)

When the scene is too dark, the image is captured by illuminating an infrared light through the camera onto the scene that greatly helps with making the scene visible for the lens. It delivers color images during the day and automatically switches to the monochrome feature as the scene darkens.

OSD Menu Support

CP PLUS HD analog cameras come with their own menu using which the camera settings can be managed, for instance, the signal type can be changed and other sensor level adjustments be made.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedeted levels even when compared to international competitors.



CP-LSC-T24ML3

2.4MP IR Bullet Camera - 30Mtr.

Feature	Specification
Image Sensor	1/3" 2.4MP PS CMOS Image Sensor (0.84667 centimeter)
Minimum Illumination	Color : 0.01 lux@F2.0, AGC ON, B/W : 0 lux with IR
Effective Pixels	2.4MP (1920 x 1080)
White Balance	Auto / Manual
Lens Type	Fixed Lens
Gain Control(AGC)	Auto
Lens	3.6mm Fixed Lens
Back Light Compensation	DWDR
Electronic Shutter	Auto
Noise Reduction	3D DNR
Video format	AHD/TVI/CVI: 2M@30fps/25fps, CVBS
UTC	Support
TV System	PAL/NTSC
IR Cut Filter	Support
Day/Night	Support
IR	IR Range of 30 Mtr.
IR Number	IR LED: 42μ x 2PCS
OSD Menu	Support
Focus Control	Fixed
Power Source	DC12V±10%, 500mA
Weatherproof Standard	IP67
Operating Temperature	-10°C~ +60°C
Operating Humidity	<95% (RH), non-condensing
Storage Temperature	-20°C~ +60°C
Storage Humidity	<95% (RH), non-condensing

THINK SECURITY
THINK CP PLUS

 CP PLUS

Feature	Specification
Dimension	169 mm x 67.5 mm x 70 mm
Casing	Metal
Weight	0.500 Kg

Company Name:

CP PLUS (Aditya Infotech Ltd.)
F-28 Okhla Industrial Area, Phase 1,
New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com



**Product casing and specifications are subject to change without prior notice*